(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 12 September 2003 (12.09.2003)

PCT

(10) International Publication Number WO 03/075083 A1

(51) International Patent Classification⁷: G02F 1/13357, H04N 9/31

(21) International Application Number: PCT/IB03/00484

(22) International Filing Date: 12 February 2003 (12.02.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 02075863.7 6 March 2002 (06.03.2002) EF

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HIKSPOORS, Henricus, M., J. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA

Eindhoven (NL). SMITS, Willem, H. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DE VAAN, Adrianus, J., S., M. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(74) Agent: VAN DEN HOOVEN, Jan; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 ΛΛ Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: PROJECTION DEVICE HAVING AN INCREASED EFFICIENCY



(57) Abstract: The invention relates to a projection device for projecting an image, comprising a light source (1), a LCD projection subsystem (3) and a projection means (4, 5) for projecting the image. A small-sized and low-cost projection device is porposed wherein said projection subsystem comprises: a waveguide integrator (30) for guiding light from an entrance (31) to an exit (34), the inner entrance surface (33) of said integrator (30) being coated with a reflective material and having a hole (32) for coupling light emittedfrom said light source (1) into said integrator (30), a reflective polarizer (35) provided at the exit surface (34) of said integrator (30) for reflecting light having the wrong polarization backinto said integrator (30), a transmissive LCD (36) provided at the exit of said reflective polarizer (35) for modulating the lighttransmitted by said polarizer (35), said LCD (36) having an integrated reflective color filter array (37) for reflecting light having the wrong color back into said integrator (30).

VO 03/075083 A1